

RAILING CAPS

Aluminum

Extruded, 6063-T52, Mill Finish. Suitable for Anodizing.

Brass

C27000, Yellow Brass, Satin or Polished Finish.

Stainless Steel

Type 304, Satin or Polished Finish. Inquire regarding Type 316.

WAGNER RAIL SYSTEM


GLASS RAILING

CABLE RAILING

SPIRAL STAIRS BALCONIES

ALUMINUM RAILINGS

BRASS / SS FITTINGS



ROLL FORMED CAP RAIL

18' Lengths

These stainless steel sections have no visible seam. For use with 1/2" glass or Wagnerail Panels. See page 23 to 29.


a	b	Satin Stainless	Polished Stainless
1.66"	1"	GR3166.4	GR3166.7
1.90"	1 1/4"	GR3190.4	GR425V.7
2.00"	1 1/4"	GR3200.4L	GR3200.7
2.50"	1 1/4"	GR3250.4L	GR3250.7

.4 indicates a circumferential satin finish
.4L indicates a longitudinal satin finish.
Suitable For Bending



Aluminum Cap Rail

Stainless Steel Cap Rails




U-CHANNEL CAP RAIL

.062" Thick, 10' Lengths

a	b	t	Satin Stainless	Polished Stainless
3/4"	7/8"	1/2"	GR30915.4	GR30915.7
1"	1 1/8"	3/4"	GR31115.4	GR31115.7

The **U-Channel Cap** protects the glass edge and secures glass panels together. Use with **PVC Inserts GR9394** or **GR9395** with **Silicone GR95CBL** to secure glass. Many local codes require that the **Glass Cap Railing** meet a specific load requirement. Confirm with your local authorities prior to specifying the use of this **Glass Cap** style.




EXTRUDED CAP RAIL

20' Lengths

a	b	t	Aluminum	Satin Aluminum	Satin Anodized Aluminum
1.66"	1"	.109"	GR2166	GR2166.4	GR2166.4AN
1.90"	1 1/4"	.109"	GR2190	GR2190.4	GR2190.4AN
2.00"	1 1/4"	.125"	GR2200	GR2200.4	GR2200.4AN
2.50"	1 1/4"	.125"	GR2250	GR2250.4	GR2250.4AN


Suitable For Bending



PROTECTIVE INSERT

a	b	c	Length	PVC
3/8"	3/4"	1"	5'	GR9396-5
1/2"	3/4"	1"	5'	GR9397-5
1/2"	3/4"	1 1/4"	5'	GR9394-5
3/4"	7/8"	1 1/4"	5'	GR9395-5

These **Inserts** protect the top edge of the glass from making contact with the metal rail cap. Secure with **GR95CBL Silicone**. Choose based on depth of **Cap Rail** and thickness of panel.




DRAWN CAP RAIL

16' Lengths

a	b	Satin Brass	Polished Brass
2.00"	7/8"	GR420V.4	GR420V.7
2.50"	7/8"	GR425V.4	GR425V.7

Suitable For Bending




SLOTTED TUBE INSERT

This insert is useful in closing up gaps between **Light Strips, Brackets** and **Mounting Clips** within the **Cap Rail** slot. Apply silicone sealant/adhesive to interior of channel on **Slotted Cap Rail** and insert as required.

Part Number
Neoprene LU001

Available in one foot increments.



ROLL FORMED CAP RAIL

10' Length, except as noted

Two roll formed sections are welded together to provide this configuration. For 1/2" or 3/4" glass, as noted. -14 after the number indicates 14' lengths.

a	b	c	glass	t	length	Satin Stainless	Polished Stainless	Satin Brass	Polished Brass
1.50"	1"	5/8"	1/2"	.050"	10'	GR315L.4	GR315L.7	GR415L.4	GR415L.7
2.00"	1 1/2"	3/4"	1/2"	.050"	10'	GR320L.4	GR320L.7	GR420L.4	GR420L.7
2.00"	1 1/2"	7/8"	3/4"	.050"	10'	GR3207.4	GR3207.7		
2.00"	1 1/2"	7/8"	3/4"	.050"	14'	GR3207.4-14	GR3207.7-14		
2.50"	1 1/2"	3/4"	1/2"	.065"	10'	GR325L.4	GR325L.7	GR425L.4	GR425L.7
2.50"	1 1/2"	7/8"	3/4"	.062"	10'	GR3257.4	GR3257.7		
2.50"	1 1/2"	7/8"	3/4"	.062"	14'	GR3257.4-14	GR3257.7-14		
3.00"	1 1/2"	3/4"	1/2"	.065"	10'	GR330L.4	GR330L.7	GR430L.4	GR430L.7
3.50"	1 1/2"	3/4"	1/2"	.065"	10'	GR335L.4	GR335L.7	GR435L.4	GR435L.7
4.00"	1 1/2"	3/4"	1/2"	.065"	10'	GR340L.4	GR340L.7	GR440L.4	GR440L.7